

# Data Sheet – PALIGHT™ PRINT

Flat Foamed PVC Sheet



## Product Definition

Flat foamed PVC sheet

## Thickness Range

2 to 10mm

## Colors

White

## Width (standard sizes)

1220 mm

1560 mm

2030 mm

- Custom colors and sizes are available upon request, possibly subject to minimum order size.

## Flammability

Standard	Classification
EN 13501	B, s2-3, d0

- All the above depends on thickness, for additional information please contact PALRAM.

## Typical Physical Properties

Property	Standard	Conditions	Unit	Value
Thickness				3mm 10mm
<b>Physical</b>				
Specific gravity	ASTM D-792		g/cm <sup>3</sup>	0.52 0.49
Water absorption	ASTM D-570	24 hr @ 23°C	%	0.5 0.8
<b>Mechanical – Machine direction</b>				
Flexural modulus	ASTM D-790		MPa	1100
Shore hardness	ASTM D-790			40
<b>Thermal</b>				
Service temperature range			C°	-10 to 55
Heat deflection temperature	ASTM D-648	Load: 1.82 MPa	C°	59-63
VICAT softening temperature	ASTM D-1525	Load: 1 Kg	C°	74-78
Coefficient of linear thermal expansion	ASTM D-696		10 <sup>-5</sup> /°C	6.7
Thermal conductivity	ASTM C-177		W/mk	0.07
<b>Electrical</b>				
Surface resistance	ASTM D-257		Ohm	5X10 <sup>15</sup>
Volume resistance	ASTM D-257		Ohm-cm	2.6X10 <sup>15</sup>